



ARROWHEAD
CONVEYOR CORPORATION

ArrowSelect®
Table Top and Mat Top Conveyor

3255 Medalist Drive
Oshkosh, Wisconsin 54902

Phone: 920-235-5562
FAX: 920-235-3638

inquiry@arrowheadsystems.com
www.arrowheadsystems.com

ArrowSelect®

Quick Ship Conveyor



Today more than ever, companies need fast delivery of quality equipment at a competitive price. Arrowhead Conveyor provides all these benefits with the ArrowSelect® line of modular table top and mat top conveyors.

ArrowSelect® is a versatile line of industrial-duty conveyor modules.

Customers in many different industries—food, personal products, paper, beverage, petrochemical, and automotive—count on their ArrowSelect® conveyors for reliable operation in a wide range of production environments.

The modular design of ArrowSelect® allows Arrowhead Conveyor to deliver your equipment quickly. Lead times are compressed to a matter of days instead of weeks. Modular design also gives customers the flexibility to adapt their ArrowSelect® systems quickly and easily to accommodate new layout requirements in the future. This helps ensure maximum return on their equipment investment.

ArrowSelect® offers tremendous flexibility, with a wide range of chain widths, options, and accessories available to allow customers to satisfy almost any layout or handling requirement. ArrowSelect® conveyors are available in both painted mild steel or stainless steel construction, so customers can select the equipment they need for either wet or dry applications.



ARROWHEAD
CONVEYOR CORPORATION

ArrowSelect®
Table Top and Mat Top Conveyor

Features and Specifications

- **Quick Delivery:** Standard components are stocked or available on JIT delivery.
- **Optimum Quality:** Finished modules are manufactured to exact tolerances and inspected prior to shipment to ensure consistent, industry-leading quality.
- **Rugged Design:** Heavy-duty stainless steel or painted mild steel construction.
- **Flexibility:** Full array of accessories and upgrades in multiple chain widths, such as guide rail types and profiles, support styles, fixed or variable speed motor packages, transfer aids, drive ends, idle ends, curves, transfer units, and incline/decline modules.
- **Easy Installation:** Modules are shipped completely assembled for quick, easy installation.
- **Maximum Value:** Manufactured with other Arrowhead Conveyor product lines using quality components and benefiting from large purchase volume—resulting in greater savings.

	Standard Specifications	Available Options
Frame Construction	Open Top	N/A
Frame Material	Hot Rolled Mild Steel with Steel-it grey color match paint	Stainless Steel with #4 polish
Standard Modules	Table top: Idle Ends, Drive Ends, 30°, 45°, and 90° Turns Mat top: Idle Ends, Drive Ends	Table top: Inline Transfers, Parallel Transfers, Copes Mat top: Parallel Transfers, 90° Transfers, Copes
Chain Return	PVC Roller with Delrin end bearings	Serpentine
Intermediate Frame Depth	Table top: 5.5" Mat top: 7"	Table top: 6.5"
Frame Depth	Table top: 8" Drive, Idle, & Parallel Transfer with End Caps Mat top: 9" deep Drive, Idle, & Parallel Transfer, 15" deep 90° Transfers	N/A
Wearstrips	Table top: UHMW Clip-on Mat top: UHMW with Steel Backup	N/A
Bearings	Two-hole, Flange Mounted, Cast Housing	Polymer Housing
Guide Rail Brackets	Adjustable Slotted Steel "L"-Brackets	N/A
Guide Rails	SS Channel with Round or Flat UHMW Insert	Table top: Arrowglide Aluminum with Round or Flat UHMW Profile
Drive Mount	Shaft / Flange Mounted—RH or LH	Table top: Adjustable Below Mount
Speeds	Table top: Fixed at 30, 60, 90 120 and 150 (Motors are inverter-duty) Mat top: Fixed at 44, 53, 66, 89, 106, 133, 177, 266	Compact VFD mounted to Drive End, 90 VDC Motor with Controller
Standard Lengths	Table top: 1'-0" and 3'-0" Idle Ends, 3'-0" Drive Ends, Standard Turns have 24" Radius and 6" Tangents Mat top: 18" and 48" Idle Ends, 48" Drive Ends, 48" or 72" Parallel Transfers	Table top & Mat top: Intermediate sections available in 1" increments from 6" to 10'-0", 18" Table top: 18" Radius for 3.25" Curves, 0" Tangent on one end of Turns
Supports	1.5" x 1.5" MS and SS Angle with Welded Cross Members and Adjustable Foot	1.5" Square Tube with Threaded Rod for Adjustment
Height Range	27" - 57", +/- 2"	N/A
Shafts	Table top: 1" diameter Steel with .25" keyway Mat top: 1.44" diameter Steel with .38" keyway	N/A
Table Top Chain Widths	Table top: 3.25", 4.5", 7.5", 10", 12" and Dual 7.5" Mat top: 3.25", 4.5", 7.5", 12", 15", 18", 24"	N/A
Chain Types	Straight Running	Table top: Side Flexing
Chain Material	Table top: Delrin Mat top: HP Plastic	Table top: LF Plastic, HP Plastic, MS, SS
Other Options	N/A	Roller Deadplates, SS Deadplates, Flush Side Areas, .75" Side Transfer Deadplates (Table top), 1.25" Side Transfer Deadplates (Mat top)

3255 Medalist Drive
Oshkosh, Wisconsin 54902

Phone: 920-235-5562
FAX: 920-235-3638

inquiry@arrowheadsystems.com
www.arrowheadsystems.com

Your Local Representative: